

15" Touch Monitor

Features

- Sleek and stylish design
- Resistive Touch
- Smart Cable Management
- Detachable Stand / Support VESA mounting
- Spill proof & Anti-dust
- Support 2nd Display & MSR



M437



Adjustable Viewing angle up to 80degrees



Smart cable management



In visual OSD button control on rear cover



Spill proof at front and rear cabinet

Specifications

| Model | M437RA | M437RB |
|------------------------------|--|-----------------------|
| Display Size | 15" | |
| Optimal Resolution | 1024 * 768 | |
| Panel Brightness | 250 cd/m ² (typ) | |
| Contrast Ratio | 600:1 | |
| Response Time | 8 ms (typ) | |
| Viewing Angle | 160°(H)/160°(V) | |
| Input Video signal | D-Sub 15 pins | D-Sub 15 pins / DVI-D |
| Touch Function | USB | USB or RS232 |
| Power consumption | 20W operation / 3W standby | |
| Input Frequency | Horizontal: 31.5-60.2 kHz ; Vertical : 56.3Hz~75Hz | |
| Power supply | DC 12V +/- 10% | |
| Temperature | Operating : 0°C~40°C ; Storage : -10°C~50°C | |
| Humidity | Operating : 20%~80% ; Storage : 10%~90% | |
| Weight | 4.67 kgs (net) | |
| Physical Dimension WxHxD(mm) | 365.2 (W) * 338.6 (H) * 200 (D) | |
| Optional | OT Series 2nd Display, Wall mount, MSR | |

Product specification subject to change without prior notice.

OTEK SYSTEM CO., LTD.

Address: 6F, 30 Sinjhong Rd., Neihu District, Taipei 114, Taiwan Tel: 886-2-7720-1688 Fax: 886-2-7721-2188
<http://www.oteksys.com> sales@oteksys.com

M437a-1110

